





Gruvlok offers a variety of pressure responsive gasket styles. Each serves a specific function while utilizing the same basic sealing concept. Proper installation of the gasket compresses the inclined gasket lips on the pipe O.D., forming a leak-tight seal. This sealing action is reinforced when the gasket is encompassed and compressed by the coupling housings. The application of internal line pressure energizes the elastomeric gasket and further enhances the gasket sealing action.




### “C” STYLE

The “C” Style cross section configuration is the most widely used gasket. It is the gasket style provided as standard in many Gruvlok Couplings (Fig. 7000, 7001, 7003, 7004HPR, 7307, 7400 and 7401). Grade “E” and “T” are standard grades while other grades are available for special applications.




### FLUSH GAP®

Designed to prohibit contaminants from building up in the gasket cavity. The centering rib fits flush over the gap between the two pipe ends thus closing off the gasket cavity. It can be used with Fig. 7000, 7001, 7003, 7004, 7400 and 7401 Couplings for many applications. Recommended for use in dry fire protection systems. Not recommended for temperatures above 160°F.




### REDUCING COUPLING

The centering rib allows for pipe positioning and serves to keep the smaller pipe from telescoping during installation. Used only with the Fig. 7010 Reducing Coupling.




### FLANGE

A specially designed gasket for the Fig. 7012, 7013 and 7312 Flange provides for a reliable seal on both the pipe and the mating flange.



### SOCK-IT®

Used in Sock-It fittings only, this pressure energized gasket provides a leak-tight seal on plain end seal pipe. Available in Grade “E” material only.



### CLAMP-T®

These gaskets conform to the curved exterior of the pipe to provide a pressure responsive seal. This unique design is only used with Fig. 7045, 7046 Clamp-T and Fig. 7047, 7048, and 7049 Clamp-T Crosses.

