



**GUARDIAN**

FIRE EQUIPMENT, INC.  
MIAMI, FL

Ph. 800.327.6584 • Fax 800.827.3869

## DETAIL AND SUBMITTAL SHEET

# 6400 Series - Fire Dept. Inlet Connections - Accessories

Project/Location: \_\_\_\_\_

Date: \_\_\_\_\_

Architect/Engineer: \_\_\_\_\_

Qty: \_\_\_\_\_

Contractor: \_\_\_\_\_

*Appropriate Selection*

**Plugs and Break Caps** - Used to keep fire dept. inlet connections free of debris and protect female threads.

Model No.	Configuration
<input type="checkbox"/> 6402	1 1/2" cast brass* plug with chain
<input type="checkbox"/> 6404	2 1/2" cast brass* plug with chain

Optional Finish:

- B Polished Brass     -C Rough Chrome Plated  
 -D Polished Chrome Plated

Threads:  NST     Other \_\_\_\_\_

Model No.	Configuration
<input type="checkbox"/> 6406	2 1/2" alum. break cap
<input type="checkbox"/> 6407	2 1/2" plastic break cap
<input type="checkbox"/> 6408	2 1/2" alum. adj. plug
<input type="checkbox"/> 6409	2 1/2" plastic adj. plug



6402/6404

**Cover Sleeve** - Used to conceal incoming pipe of free-standing fire department connection.

Model No.	Configuration
<input type="checkbox"/> 6414	4" x 18"
<input type="checkbox"/> 6416	6" x 18"


Optional Finish:  -D Polished Chrome Plated

**Clappered Snoots** - Used on fire department inlet connections to check backflow. Cast brass body, polished trim.

Model No.	Configuration
<input type="checkbox"/> 6418	2 1/2" female swivel inlet x 3" female NPT outlet
<input type="checkbox"/> 6419	2 1/2" female swivel inlet x 3" male NPT outlet

Optional Finish:  -D Polished Chrome Plated trim

Threads:  NST     Other \_\_\_\_\_



6406/6407



6408/6409



6414/6416

**Swing Check Valve** - Used to prevent water backflow, UL listed/FM approved

Model No.	Configuration
<input type="checkbox"/> 6420	4" groove x groove, cast brass
<input type="checkbox"/> 6421	4" NPT male x groove, cast brass
<input type="checkbox"/> 6422	4" NPT male x NPT female, cast brass



6418



6419

**Wafer Check Valve** - Used to prevent water backflow, UL listed/FM approved

Model No.	Configuration
<input type="checkbox"/> 6426	4" cast iron
<input type="checkbox"/> 6428	6" cast iron



6420-6422

**Automatic Ball Drip** - Used to drain water from the low point of the system

Model No.	Configuration
<input type="checkbox"/> 6430	1/2" NPT, male x male, straight, cast brass
<input type="checkbox"/> 6431	1/2" NPT, male x male, angle, cast brass
<input type="checkbox"/> 6432	3/4" NPT, male x male, straight, cast brass
<input type="checkbox"/> 6433	3/4" NPT, male x male, angle, cast brass



6426/6428

**Sillcock** - Used to manually drain water from low point or washdown

Model No.	Configuration
<input type="checkbox"/> 6435	3/4" female NPT x male GHT, cast brass

Optional Finish:  -D Polished Chrome Plated



6430/6431



6435